

minCam mc15 Push Camera

The mC15 is a compact and durable CCTV push camera system. Equipped with the 0.71" diameter KK18 camera and flexible 5.8mm push rod for maneuverability in small diameter and tight-turn radius pipe inspections.

- Application range: 1.2" to 5"
- 512 Hz sonde standard (33 KHz optional).

System Specifications

- 100 ft. (30m) of flexible 5.8mm push cable.
- 512 Hz sonde standard (33 kHz special order)
- Electronic on-screen distance counter.
- Lithium Ion battery for more than 2 hours operation.
- Power Supply: 100 - 240V AC; 12V DC Car adapter.
- Lightweight stainless steel & carbon reel cage.
- Control unit: On/off switch, light regulation, distance counter reset, battery level LEDs, BNC video out.
- Mechanical reel brake.
- Weight: 17 lbs.; Dimensions: 14" x 16" x 9" (L x H x W)

Monitor & Recording

- 5.6" TFT LCD monitor records video, voice, & photo.
- Remote control for recording and system operation.
- Ball joint attachment to reel.
- SD card reader, max. 32 GB for approx. 20 hours of video.
- MPEG-4 Video (.avi, 800x600); Pictures (.bmp 640x480)
- External Qwerty keyboard available (special order).

Camera KK18

- Range: 1.2" - 5"
- Straight-forward color camera
- High-resolution 480 TVL
- 10 pcs LEDs
- 2mm sapphire glass lens
- Water tight up to 72.5 psi
- Outer diameter: 0.71"
- Cylindrical length: 0.39"

minCam

