

minCam mc30 Push Camera

The mc30 features our smallest auto-upright color camera, the 29mm (1.14") KK29SL which is connected to 100 ft. of 6.7mm fiberglass push cable. Integrated photo, video, and voice recording to SD card.

- Application range: 2" to 8"
- 512 Hz sonde standard (33 KHz optional).

System Specifications

- 100 ft. (30m) of fiberglass 6.7mm push cable.
- 512 Hz sonde standard (33 kHz special order)
- Electronic on-screen distance counter.
- Lithium Ion battery for more than 2 hours operation.
- Power Supply: 100 - 240V AC; 12V DC Car adapter.
- Lightweight stainless steel & carbon reel cage.
- Control unit: On/off switch, light regulation, distance counter reset, battery level LEDs, BNC video out.
- Mechanical reel brake.
- Weight: 20 lbs.; Dimensions: 17" x 19" x 9" (W x H x D)

Monitor & Recording

- 5.6" TFT LCD monitor records video, voice, & photo.
- Remote control for recording and system operation.
- Ball joint attachment to reel.
- SD card reader, max. 32 GB for approx. 20 hours of video.
- MPEG-4 Video (.avi, 800x600); Pictures (.bmp 640x480)
- External Qwerty keyboard available (special order).
- 8.4" sunlight readable monitor available (special order).

Camera KK29SL

- Range: 2" - 8"
- Auto-upright color camera
- High-resolution 480 TVL
- 10 pcs LEDs
- 3mm sapphire glass lens
- Water tight up to 145 psi
- Outer diameter: 1.14"
- Cylindrical length: 0.63"

minCam

