

## minCam mc50 Push Camera

*The mC50 comes with the KK55SL auto-upright 2" camera, which can pass through 90° bends from 4" onwards and inspect pipe diameters up to 16" with the optional large roller upgrade.*

- Application range: 3" to 16"
- 512 Hz sonde standard (33 KHz optional).

### System Specifications

- 200 ft. (60m) of 9.2mm fiberglass push cable (up to 260 ft.)
- 512 Hz sonde standard (33 kHz special order)
- Electronic on-screen distance counter.
- Lithium Ion battery for more than 1.5 hours operation.
- Power Supply: 100 - 240V AC; 12V DC Car adapter.
- Lightweight stainless steel & carbon reel cage.
- Control unit: On/off switch, light regulation, distance counter reset, battery level LEDs, BNC video out.
- Mechanical reel brake.
- Weight: 35 lbs.; Dimensions: 25" x 26" x 12" (L x H x W)

### Monitor & Recording

- 8.4" TFT LCD sunlight-readable, records video, voice & photo.
- Pelican® Storm Case heavy-duty housing.
- Ergonomically attached to reel.
- SD card reader, max. 32 GB for approx. 20 hours of video.
- MPEG-4 Video (.avi, 800x600); Pictures (.bmp 640x480)
- Integrated Qwerty keyboard available (special order)

### Camera KK55SL

- Range: 3" - 16"
- Auto-upright color camera
- High-resolution 480 TVL
- 16 pcs LEDs
- 4mm sapphire glass lens
- Water tight up to 145 psi
- Outer diameter: 2.17"
- Cylindrical length: 1.42"

**minCam**

